



High Performance Seating

high-productivity, long-lasting, powerfully ergonomic chairs



REDESIGNED TO BE THE BEST



11800 HIGH BACK

The 11800 set the standard for 24/7 Intensive Use Chairs. The first chair to combine state of the art ergonomics with unmatched durability; the newly redesigned 3142rl is raising the bar for 24/7 chairs, now offering quick-change



KEY POINTS

ERGO AIR SUSPENSION SYSTEM™

Our Ergo Air Suspension (EAS2)™ dissipates the occupant's weight over the entire chair surface improving blood flow and increasing oxygen levels to tissues. Improved blood flow and increased oxygen levels improves concentration and productivity and decreases fatigue. EAS2 conforms to the shape of each occupant, as it almost instantly bounces back to original shape when weight is lifted. No springs eliminates the chances of squeaky or flattened springs.

REPLACEABLE COVERS – Covers can wear, but our frames are virtually indestructible. Bring back that 'brand new' look in minutes even after years of 24/7 service. Covers are held on by hook-and-loop and can be replaced in a matter of minutes.

SAFETY CASTERS- Smooth dual wheel design with spring action not to roll away unless there is weight in the chair. Dual connection point eliminates rattle for a smooth roll.

ALL STEEL FRAME - Ten gauge steel maintains original tensile strength and rigidity over years of 24/7 heavy duty use.

ADJUSTABLE ARMRESTS - No tools required to adjust. You can choose style, width and height for customized comfort, security, and support. Swing arm style will swing out of the way from a seated position.

WARRANTY - The best warranty you'll never need. Chair is covered by a 6 year warranty that includes all normal wear and tear. Chair is covered by a 10 year warranty that includes all manufacturing defects in materials and/or workmanship. Weight limit is 550 lbs. in a multi-shift environment.

11800 HIGH BACK



SEAT PAN DEPTH	19"
SEAT PAN WIDTH	20.5"
BACK HEIGHT - TO TOP OF CHAIR BACK	25"
BACK HEIGHT - TO TOP OF HEADREST	31"
ARM HEIGHT ADJUSTMENT RANGE	7 POSITIONS (3.5") OR INFINITE ADJUSTMENT
ARM WIDTH ADJUSTMENT RANGE	2.5" (22"-27")
PNEUMATIC CYLINDER SPECIFICATION	CERTIFIED TO 100,000 CYCLES 500 NEWTONS - DIN CLASS 4551-4
TILT CONTROL W/ TENSION ADJUSTMENT AND UPRIGHT POSITION LOCK	YES
UPRIGHT POSITION LOCK	YES
BASE SIZE DIAMETER AND CONFIGURATION	28" AND 7 LEG (TESTED TO 10,000 LB. DYNAMIC LOAD)
LUMBAR SUPPORT ADJUSTMENT	INFINITE ADJUSTMENT FROM SEATED POSITION
ARMREST CHOICES	C-LOOP OR OPTIONAL SWING ARMS OR FIXED
FRAME CONSTRUCTION	10 GAUGE STEEL
SEAT BOTTOM ASSEMBLY	ERGO AIR SUSPENSION (EAS ²)™
SEAT BACK ASSEMBLY	ERGO AIR SUSPENSION (EAS ²)™
CASTERS	SAFETY CASTER, DUAL CONNECTION POINT 165 LB./CASTER - OPTIONAL 75mm, GLIDES OR ESD CASTERS
COVER MATERIALS	STACCATO OR OPTIONAL LEATHER AND ALTERNATIVE LEATHER
REPLACEABLE COVERS	YES
TEST STANDARDS	30% HIGHER: GSA FNEW83-269A and ANSI/BIFMA X5.11 STANDARD TEST: ANSI/BIFMA and FIRA 055:2005
WARRANTY	6 YEAR 24/7 INTENSIVE USE WARRANTY - INCLUDES NORMAL WEAR AND TEAR - 10 YEAR ON FRAME
ADJUSTABLE NECK ROLL	CLOTH OR LEATHER
EMBROIDERY	CUSTOM EMBROIDERY AVAILABLE

BEST OF BOTH WORLDS



11838 OPERATOR

This unique 24/7 intensive use chair combines the utility of a task chair with the comfort of a high back. Lean against the headrest or neck roll or slide the headrest out of the way and lock the chair with a forward tilt for additional support while doing desk work.



KEY POINTS

ERGO AIR SUSPENSION SYSTEM™

Our Ergo Air Suspension (EAS2) dissipates the occupant's weight over the entire chair surface improving blood flow and increasing oxygen levels to tissues. Improved blood flow and increased oxygen levels improves concentration and productivity and decreases fatigue. EAS2 conforms to the shape of each occupant, as it almost instantly bounces back to original shape when weight is lifted. No springs eliminates the chances of squeaky or flattened springs.

REPLACEABLE COVERS - Covers can wear, but our frames are virtually indestructible. Bring back that 'brand new' look in minutes even after years of 24/7 service. Covers can be held on by hook-and-loop and can be replaced in a matter of minutes. Back rest requires a screwdriver.

SAFETY CASTERS - Smooth dual wheel design with spring action not to roll away unless there is weight in the chair. Dual connection point eliminates rattle for a smooth roll.

ALL STEEL FRAME - Ten gauge steel maintains original tensile strength and rigidity over years of 24/7 heavy duty use.

ADJUSTABLE ARMRESTS - No tools required to adjust. You can choose style, width and height for customized comfort, security, and support. Swing arm style will swing out of the way from a seated position.

WARRANTY - The best warranty you'll never need. Chair is covered by a 6 year parts only warranty that includes all normal wear and tear. Chair is covered by a 10 year warranty that includes all manufacturing defects in materials and/or workmanship. Weight limit is 550 lbs. in a multi-shift environment.

11838 OPERATOR



SEAT PAN DEPTH	18" (ADJUSTABLE TO 21")
SEAT PAN WIDTH	21"
BACK HEIGHT - TO TOP OF CHAIR BACK	21"-24"
BACK HEIGHT - TO TOP OF HEADREST	27"-31.5"
ARM HEIGHT ADJUSTMENT RANGE	7 POSITIONS (3.5") OR INFINITE ADJUSTMENT
ARM WIDTH ADJUSTMENT RANGE	2.5" (22"-27")
PNEUMATIC CYLINDER SPECIFICATION	CERTIFIED TO 100,000 CYCLES 500 NEWTONS - DIN CLASS 4551-4
ARTICULATING HEADREST	USE AS A NECK ROLL, HEADREST, OR FOLD OUT OF THE WAY
TILT CONTROL W/ TENSION ADJUSTMENT AND UPRIGHT POSITION LOCK	YES
UPRIGHT POSITION LOCK	YES
BASE SIZE DIAMETER AND CONFIGURATION	28" AND 7 LEG (TESTED TO 10,000 LB. DYNAMIC LOAD)
LUMBAR SUPPORT ADJUSTMENT	INFINITE ADJUSTMENT FROM SEATED POSITION
ARMREST CHOICES	C-LOOP OR OPTIONAL SWING ARMS OR FIXED
FRAME CONSTRUCTION	10 GAUGE STEEL
SEAT BOTTOM ASSEMBLY	ERGO AIR SUSPENSION (EAS ²)™
CASTERS	SAFETY CASTER, DUAL CONNECTION POINT 165 LB./CASTER - OPTIONAL 75mm, GLIDES OR ESD CASTERS
COVER MATERIALS	STACCATO OR OPTIONAL LEATHER AND ALTERNATIVE LEATHER
REPLACEABLE COVERS	YES
TEST STANDARDS	30% HIGHER: GSA FNEW83-269A and ANSI/BIFMA X5.11 STANDARD TEST: ANSI/BIFMA and FIRA 055:2005
WARRANTY	6 YEAR 24/7 INTENSIVE USE WARRANTY - INCLUDES NORMAL WEAR AND TEAR - 10 YEAR ON FRAME
EMBROIDERY	CUSTOM EMBROIDERY AVAILABLE



11775 ULTRA CHAIR 24-7



Arms standard
with chair

KEY POINTS

RATED WEIGHT CAPACITY:	350Lbs	ADJUSTABLE LUMBAR:	Upper & lower manual air lumbar
WEIGHT:	55Lbs	ADJ.ARM HEIGHT:	8" tilt adjustment
MATERIAL:	Black Leather	SEAT PAN ANGLE:	Seat cushion has 6 degree front angle adjustment
OVERALL DEPTH:	24.75" with back cushion at 90° to seat and 31.5" with back cushion fully reclined	CASTERS:	2.5" Double wheel castors
OVERALL WIDTH:	25.75" with arms 20.75" without arms	PNEUMATIC PUMP:	Gas cylinder mechanism
OVERALL HEIGHT:	47.75" to 51.75" with head rest and back cushion at 90° to seat cushion	TENSION CONTROL:	Side tension adjustment which allows the user to adjust the tension from the seated position
SEAT WIDTH:	20.75"	FEATURES:	<ul style="list-style-type: none">• Adjustable headrest• 2.5" adjustable standard armrest• Seat back angle adjustment• Liquicell seat technology• Tilt rocker adjustment• Weight adjustment• Five star base• Steel frame• Front tilt adjustment
BACK WIDTH:	20"		
WIDTH BETWEEN ARMS:	20"		
BASE CIRCUMFERENCE:	30.5"		



11746 24/7 HIGH BACK



Arms standard
with chair

KEY POINTS

RATED WEIGHT CAPACITY: 300Lbs

WEIGHT: 48Lbs

CARTON DIMENSIONS: 110.8 Cubic Feet

SEAT DIMENSIONS: 19"Width x 15 1/2"-18 1/4" Depth
17"-21 1/4" Height From floor

BACK DIMENSIONS: 23 1/2" - 18"

OVERALL DIMENSIONS: Max chair width 26"
Max chair depth 25"
Chair height 37 3/4" - 40"

COUNTRY OF ORIGIN: USA

CASTERS - CARPET: Monochromatic, black color only, open dual wheel-60 mm diameter. Made from nylon 6/6 with a steel wheel axle and socket stem

BASE: Made from injection-molded glass filled Nylon, 26" dia. The base incorporates five legs

PNEUMATIC PUMP: Gas cylinder mechanism

TILT LOCK: Features 5 settings to lock the back in various positions of recline. The tilt lock knob is conveniently located on the left side of the chair under the seat

SEAT CUSHION: The seat cushion is molded cellular urethane foam; foam density is 2.8 lbs per Cu. Ft. (ILD is 41 lbs). The minimum seat cushion thickness is 2-3/4"

MESH BACK: Breathable mesh back supports you through various movements

ARMS: Height and width adjustable arms, multi-adjustable arms

FIRE CODE: Meets CAL 133 Fire code



11761 TASK CHAIR



Arms standard
with chair

KEY POINTS

RATED WEIGHT CAPACITY:	250Lbs	CASTERS - CARPET:	High-impact dual wheel hooded casters
WEIGHT:	49Lbs	5-STAR BASE:	Nylon fiberglass composite
CARTON DIMENSIONS:	15"H x 29"W X 26"D	PNEUMATIC PUMP:	Gas cylinder mechanism
SEAT HEIGHT:	18 1/2 x 22 1/2"	COLOR:	Pattern black fabric upholstery
SEAT WIDTH:	20 1/2"	FEATURES:	Tention adjustment, chair tilt lock, seat height adjustment, back height adjustment, back angle adjustment, arm height adjustment, waterfall seat edge, properly contoured cushions, center tilt movement
SEAT DEPTH:	19"	CERTIFICATIONS:	Greenguard certified
BACK WIDTH:	20"		
BACK HEIGHT:	23" - 24 1/2"		
ARM HEIGHT:	8" - 11"		
OVERALL DIMENSIONS:	44" - 48"H x 25 1/2"W x 25" D		
COUNTRY OF ORIGIN:	USA		